


12	OG	QVR	0.5mm ²	24	BU	2	AVSS	1.0mm ²	36	GN	RD	AVSS	0.5mm ²	48	BU	QVR	0.75mm ²					
11	BN	QVR	0.5mm ²	23	GN	BK	4	AVSS	0.5mm ²	35	YE	BK	4	QVR	0.5mm ²	47	GY	WH	AVSS	0.5mm ²		
10	GN	YE	QVR	0.5mm ²	22	BN	2	AVSS	0.5mm ²	34	OG	BK	3	QVR	0.5mm ²	46	BU	WH	AVSS	0.5mm ²		
9	RD	WH	QVR	0.75mm ²	21	GN	OG	AVSS	0.5mm ²	33	RD	BK	2	QVR	0.5mm ²	45	BN	GY	AVSS	0.5mm ²		
8	LT	GN	QVR	0.5mm ²	20	YE	RD	QVR	0.5mm ²	32	BN	BK	1	QVR	0.5mm ²	44	OG	WH	AVSS	0.5mm ²		
7	GY	QVR	0.5mm ²	19	BU	GY	AVSS	0.5mm ²	31	LT	GN	RD	QVR	0.5mm ²	43	BK	YE	AVSS	0.5mm ²			
6	GN	AVSS	1.0mm ²	18	YE	3	QVR	1.0mm ²	30	VT	WH	AVSS	0.5mm ²	42	BN	BU	AVSS	0.5mm ²				
5	BK	AVSS	1.0mm ²	17	YE	2	QVR	1.0mm ²	29	VT	AVSS	0.5mm ²	41	BN	WH	AVSS	0.5mm ²					
4	WH	RD	AVSS	1.0mm ²	16	YE	1	QVR	1.0mm ²	28	BK	WH	AVSS	0.5mm ²	40	GN	GY	AVSS	0.5mm ²			
3	BK	RD	QVR	1.0mm ²	15	YE	WH	QVR	0.5mm ²	27	OG	RD	AVSS	0.5mm ²	39	BU	YE	AVSS	0.5mm ²			
2	RD	2	QVR	1mm ²	14	YE	WH	AVSS	0.5mm ²	26	BU	RD	AVSS	0.5mm ²	38	OG	GY	AVSS	0.5mm ²			
1	RD	QVR	6mm ²	13	LT	BU	QVR	0.5mm ²	25	RD	GY	AVSS	0.5mm ²	37	YE	GY	AVSS	0.5mm ²	49	WH	QVR	0.75mm ²

50CC EURO 5 VERSION



With 2 pieces Waterproof relay
CANNING THINGS SCHEMS AND TECHNOLOGY (GROUP)
CO., LTD

Main cable

DYJ-251000-F7J000